



Model C-FH– Detonation Arrestor “Stubby”



Model C-18C-FH-GD-CS-S

The Paradox “Stubby” Detonation Flame Arrestor, represents the best technology for value in flame arrestor protection, preventing flame propagation by absorbing heat and dissipating supersonic pressure waves, using multiple spiral wound crimped ribbon flame cells staged with turbulent creating screen sections. These screen sections allow for much larger cells than that of competitive crimped ribbon arresters, allowing maximum flow with maximum protection. They provide protection against flame propagation in piping systems that are manifolded or have long run-up distances. Paradox’s detonation flame arrestor element technology dampens the high velocities and pressures associated with deflagrations and detonations while quenching the flame front and providing larger flame channels which require less frequent maintenance due to clogging and greater ease in cleaning when service is required. This translates to less downtime. Our

element offers maximum flow to pressure drop characteristics enhancing the value of our product in any system. They are typically used for extended pipe length or multiple pipe bend configurations to stop high pressures and flame velocities associated with detonations and overdriven detonations. In addition, it stops confined and unconfined, low- and high-pressure deflagrations. All Paradox units are bi-directional and are proven to stop an ignited flammable vapor mixture approaching from either direction that can be traveling at subsonic or supersonic velocities.

Designed with flanged connections, this Arrestor provides the option of removal of the flame cell (element) for easy cleaning and replacement without disconnection of the pipe connection flanges. Standard housing construction is carbon steel and is available in 304 or 316 stainless steel or Hastelloy. The element is available in 304 SS, 316 SS, or Hastelloy.

This Coast Guard Approved “Stubby” version is approximately 20% shorter than the standard DFA. This unit has consistent design features throughout the size ranges with improved flow characteristics.

Special material and protective coatings are available on request.

- U.S. Coast Guard Approved 2" (50mm) - 22" (559mm) IIA (D) and IIB3 (C) Concentric and Eccentric design.
- USCG Tested to 36" (72") Concentric in IIA (D).
- IIC (B) Tested to U.S. Coast Guard, (Concentric only)
- ATEX (EN 12874 Tested) 2" (50mm) - 24" (500mm) IIA and IIB Concentric and Eccentric design.



Features and Benefits

- **USCG Approved**
- **All Paradox Detonation Flame Arrestors** are designed for stable, overdriven & unstable detonations as well as deflagrations.
- **Removable Element** design allows for easy replacement.
- **Large Inspection Ports** are **Optional** on larger models and allows for easy inspection and cleaning.
- **Stubbys are up to 20% Shorter** than standard DFA in the larger sizes; important when space is limited.
- **Outstanding corrosion** and chemical resistance.
- **Instrument/drain ports** are optional and available in 1/2", 3/4" or 1" NPTF or 125/150# ANSI Flange sizes.
- Available with Eccentric or Concentric end sections.



Paradox's Large Crimp Opening Provide:



- Maximum flow
- Less Pressure Drop
- Easy Cleaning
- Less Clogging
- Less Maintenance
- Bi-directional Design
- Available in ANSI, DIN and JIS flanges.

Material Specifications

Housing	Cell	Gas Group
Carbon Steel	304 SS	IIA (D)
304 SS	316 SS	IIB3 (C)
316L SS	Hastelloy	IIC (B)
Hastelloy		



Series C-FH Detonation Flame arrester Specifications



USCG
Approved



Model	A 150# AN-SI Conn. Size in. (mm)	B Housing Size In. (mm)	C Outside Di- ameter In. (mm)	D Overall Length In. (mm) +/- .250"	E Height In- cluding Lift- ing Lug	Approx. Weight Lb. (Kg.) Grp D +/- 10%
C-2C-FH	2 (50)	6 (150) 8 (200) Grp B	11 (279)	27.3(694)	15.5(394)	175 (79.4)
C-3C-FH	3 (75)	8 (200)	13.50 (343)	29 (736)	17.8(452)	220 (99.8)
C-4C-FH	4 (100)	10 (250)	16.00 (406)	32.25(819)	20(500)	400 (181.4)
C-6C-FH	6 (150)	12 (300)	19.00 (483)	35(889)	23(584)	525 (238)
C-8C-FH	8 (200)	16 (400)	25.50 (648)	43.25(1098.5)	31(787)	1360 (616.9)
C-10C-FH	10 (250)	20 (500)	30.50 (775)	48(1219)	35.5(902)	1945 (882.2)
C-12C-FH	12 (300)	24 (600)	36.00 (914)	53.9(1369)	40.3(1024)	3000 (1360.8)
C-14C-FH	14 (350)	28 (700)	40.75 (1035)	57.3 (1455)	45(1143)	3400 (1542.2)
C-16C-FH	16 (400)	30 (750)	43.00 (1092)	58.16(1477)	47(1194)	3800 (1723.7)
C-18C-FH	18 (450)	34 (850)	47.50 (1207)	63.1(1603)	51.4(1306)	5000 (2268)
C-20C-FH	20 (500)	36 (900)	50.00 (1270)	65 (1651)	54(1372)	5600 (2540.1)
C-22C-FH	22 (560)	36 (900)	50.00 (1270)	66 (1575)	54(1372)	5600 (2540)
C-22C(48)- FH	22(560)	48 (1200)	59.50 (1511)	101.00 (2565)	62(1574)	8400 (3810)



**Model Series “C & C-FH” Detonation Flame Arrester for
Group D, C, or B Gas
Specification Data Sheet**



United States Coast Guard Approved



Flame Arrester Type	In-line Bi- Directional Flame Arrester
Recommended installation /use	Vertically or Horizontally anywhere in a Piping systems.
Design/Test Standard/Test Gas	USCG 33 cfr/Propane/Ethylene/Hydrogen
Connection sizes	2” through 22” Pipe sizes (24” & 30” Special order).
Type of connection	Flanged connection.
Flange ratings	Available in ASME 150# Raised Faced Flange
Housing Materials	Standard Model; Carbon Steel, also available in 304, 316L & most other Austenitic metal or hastelloy.
Element Type/Material	The element is crimped metal ribbon made from 304 Stainless Steel and is also available in 316L or hastelloy.
Maximum Initial pressure (Psia.)	22.7(Grp D), 20.7,(Grp C), 19.7 (Grp B)
Operating temperature range	-17°C to +60°C
Hydrostatic Test Pressure	350 Psig.
Gas Group Application Rating	NEC Group D,C, B(IEC Group IIA, IIB, IIC)